

Compact 4L ERRP



CONDENSATE REMOVAL PUMP

Our Compact 4L Economy Retail Refrigeration Pump is designed exclusively to fit underneath retail refrigeration cabinets allowing for the removal of defrost and contaminated water.



190L/h max. flow




35m max. head

Key Features

- Lightweight & slim
- Low voltage at point of use
- 2-stage filter to prevent growth and spread of biofilm
- Plug & Play


Suitability

- Refrigeration units; cold store cabinets
- **Perfect for...** Single & multiple refrigeration units



2.82
kg

@ 230 VAC 50Hz	
Max. flow	190 L/h @ 0 head
Max. rec. head	35m
Tank capacity	4.2L
Sound level @ 1m	60 dB(A)
Power supply Input:	100~240V AC 50/60Hz
Rated	Non continuous
Class	II appliance
Max. ambient temp.	40°C / 104°F
Inlet/Outlet	40mm in, 10mm out
IP Protection	IPX4
Safety Switch	3A NC/NO
Thermal protection	✓
Flammable refrigerant compatibility	Designed to minimise spark risk
Equipment communication	Modbus RTU (option extra: FP3555)



OPTIONS	
Side inlet	FP3550
Top inlet	FP3551

Download manual at aspenpumps.com

SUGGESTED XTRA ACCESSORIES

Description	Part No.
Vinyl Tube Braided 3/8" (10 mm)	AX5101
Jallystrips	S010371



For more installation accessories take a look at our Aspen Xtra range

IN THE BOX

Low Profile ERRP pump • 2m Plug & Play power cable • 11/2" BSP connector (for 40mm ID waste pipe) • Install manual